

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
10 July 2003 (10.07.2003)

PCT

(10) International Publication Number  
**WO 03/056313 A1**

- (51) International Patent Classification<sup>7</sup>: **G01N 21/77, 21/55, 33/00**
- (72) Inventor; and  
(75) Inventor/Applicant (for US only): **BERG, Arne** [NO/NO]; Vipeveien 10, N-7082 Katten (NO).
- (21) International Application Number: **PCT/GB02/05907**
- (22) International Filing Date:  
23 December 2002 (23.12.2002)
- (74) Agents: **MARKS & CLERK** et al.; 4220 Nash Court, Oxford Business Park South, Oxford, Oxfordshire OX4 2RU (GB).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
20016358 27 December 2001 (27.12.2001) NO
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (71) Applicant (for all designated States except US): **OPTOPLAN AS** [NO/NO]; Bjørkhaugvn. 27, N-7002 Trondheim (NO).
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,
- (71) Applicant (for IS only): **HARDING, Richard, Patrick** [GB/GB]; Marks & Clerk, 4220 Nash Court, Oxford Business Park South, Oxford, Oxfordshire OX4 2RU (GB).

[Continued on next page]

(54) Title: **SENSOR SYSTEM AND METHOD**

(57) Abstract: A sensor system for the detection or measurement relating to a chemical environment, comprising an optical fibre, an optical source for launching light into the optical fibre, the sensor system being adapted to let a gas, e.g. hydrogen derived from said chemical environment, diffuse into the optical fibre. The gas thereby alters the optical properties of the optical fibre. The system comprises optical signal detection and signal analysing means adapted for determining changes in the optical properties of the optical fibre due to the in-diffusion of the said gas. The signal analysis means is adapted to derive from the determined changes at least one characteristic value representing the chemical environment.